

-30V, -45A P-CHANNEL POWER MOSFET

GENERAL DESCRIPTION

The SFD3004PT5 uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge.


It can be used in a wide variety applications.

Features

- ◆ $V_{DS} = -30V$, $I_D = -45A$
- ◆ $R_{DS(on)}$
TYP: $8.0\text{m}\Omega$ @ $V_{GS} = -10V$
TYP: $11\text{m}\Omega$ @ $V_{GS} = -4.5V$

Applications

- ◆ Power factor correction (PFC)
- ◆ Switched mode power supplies (SMPS)
- ◆ Uninterruptible power supply (UPS)
- ◆ LED lighting power



ORDERING INFORMATION

Part No.	Package	Marking	Material	Packing
SFD3004PT5	TO-252-2L	SFD3004PT5	Pb Free	Reel

ABSOLUTE MAXIMUM RATINGS (T_J=25°C unless otherwise noted)

Characteristics	Symbol	Ratings	Unit
Drain-Source Voltage	V _{DS}	-30	V
Gate-Source Voltage	V _{GS}	±20	V
Drain Current	I _D	-45	A
T _C = 100°C	I _D	-32	
Drain Current Pulsed(Note 1)	I _{DM}	-180	A
Power Dissipation(T _C =25°C)	P _D	42	W
Single Pulsed Avalanche Energy (Note 2)	E _{AS}	196	mJ
Operation Junction Temperature Range	T _J	-55~+150	°C
Storage Temperature Range	T _{stg}	-55~+150	°C
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	TL	300	°C

 THERMAL CHARACTERISTICS

Characteristics	Symbol	MAX	Unit
Thermal Resistance, Junction-to-Case	R _{θJC}	2.97	°C/W
Thermal Resistance, Junction-to-Ambient	R _{θJA}	62.5	°C/W

ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
Drain -Source Breakdown Voltage	B _{VDSS}	V _{GS} =0V, I _D =-250μA	-30	--	--	V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V	--	--	-1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =20V, V _{DS} =0V	--	--	100	nA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =-20V, V _{DS} =0V	--	--	-100	
On Characteristics						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D =-250μA	-1.0	-1.5	-2.0	V
Static Drain- Source On State Resistance	R _{DSS(on)}	V _{GS} =-10V, I _D =-15A	--	8.0	10.5	mΩ
		V _{GS} =-4.5V, I _D =-10A	--	11	15	
Dynamic Characteristics						
Gate Resistance	R _G	V _{GS} =0V, f=1.0MHZ	1	6.0	10	Ω
Input Capacitance	C _{iss}	V _{DS} =-15V V _{GS} =0V f=1.0MHZ	--	2800	--	pF
Output Capacitance	C _{oss}		--	346	--	
Reverse Transfer Capacitance	C _{rss}		--	319	--	
Switching Characteristics						
Turn-on Delay Time	t _{d(on)}	V _{DD} =-15V, V _{GS} =-10V R _G =2.5Ω, I _D =-20A	--	14	--	ns
Turn-on Rise Time	t _r		--	20	--	
Turn-off Delay Time	t _{d(off)}		--	95	--	
Turn-off Fall Time	t _f		--	65	--	

Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-20A$ $V_{GS}=-10V$	--	30	--	nc
Gate-Source Charge	Q_{gs}		--	5.3	--	
Gate-Drain Charge	Q_{gd}		--	7.6	--	

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous Source Current	I_s	Integral Revers P-N Junction Diode in the MOSFET	--	--	-45	A
Pulsed Source Current	I_{SM}		--	--	-180	
Diode Forward Voltage	V_{SD}	$I_s=-15A, V_{GS}=0V$	--	-0.8	-1.2	V

1. Pulse width limited by maximum junction temperature
2. $L=0.5mH$, $V_{DD}=-20V$, $V_G=-10V$, $R_G=25\Omega$, starting $T_J=25^\circ C$
3. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
4. Essentially independent of operating temperature

Typical Performance Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-resistance vs. Drain Current




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics








Figure 6. Gate Charge





Typical Performance Characteristics




Test Circuit


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveform




Unclamped Inductive Switching Test Circuit & Waveform



Package Dimensions of TO-252-2L



Package Dimensions of TO-252-2L



Disclaimer:

- Hi-semicon reserves the right to make changes to the information herein for the improvement of the design and performance without further notice! Customers should obtain the latest relevant information before placing orders and should verify that such information is complete and current.
- All semiconductor products malfunction or fail with some probability under special conditions. When using Hi-semicon products in system design or complete machine manufacturing, it is the responsibility of the buyer to comply with the safety standards strictly and take essential measures to avoid situations in which a malfunction or failure of such Hi-semicon products could cause loss of body injury or damage to property.
- Hi-semicon will supply the best possible product for customers!